

## SCOTCH® SUPER 88 VINYL TAPE

- All weather, premium grade vinyl tape for primary insulation up to 600 V or protective jacketing for low/medium voltage cable splices
- Aggressive adhesive and elastic backing ensures easy conformation to irregular surfaces for moisture tight electrical and mechanical protection
- Will perform in a continuous temperature environment up to 220°F (105°C)
- Conformable for cold weather applications: 0°F (-18°C)
- Thickness: 7 mil
- Colour: Black
- UL and CSA approved



Priced per Roll

Model No.	Dimensions	Roll /Case	Price /Each
PC694	3/4" x 66' (19 mm x 20.1 m)	100	

## SCOTCH® 130C LINERLESS RUBBER SPLICING TAPE

- Highly conformable, linerless self-bonding ethylene propylene rubber (EPR) tape for insulating all solid dielectric cables up to 69 kV
- Excellent thermal dissipation of splice heat
- Meets industry specifications, excellent physical and electrical properties
- Immediate moisture sealing and void-free buildups
- Rated up to 194°F (90°C) continuous operation and up to 266°F (130°C) short-term overload service
- Having no liner makes jobs easier and saves time
- Thickness: 30 mils



Priced per Roll

Model No.	Dimensions	Rolls/Case	Price/Each
AF284	3/4" x 30'	24	
XC323	1" x 30'	24	
XH307	1-1/2" x 30'	12	

## SCOTCH® 35 COLOUR CODING VINYL TAPE

- Premium grade vinyl electrical colour-coding tape for phase and job identification and safety
- Heavy-duty, premium grade
- Temperature rating: 220°F/105°C
- Thickness: 7 mil
- UL and CSA approved



Priced per Roll

Model No.	Colour	Dimensions	Rolls /Case	Price /Each
PC696	Blue	1/2" x 20'	100	
PC720	Green	1/2" x 20'	100	
PC721	Red	1/2" x 20'	100	
PC722	White	1/2" x 20'	100	
PC723	Yellow	1/2" x 20'	100	
XC309	Orange	1/2" x 20'	100	
PE118	Blue	3/4" x 66'	100	
PE120	Green	3/4" x 66'	100	
XC312	Red	3/4" x 66'	100	
PE119	White	3/4" x 66'	100	
XC314	Yellow	3/4" x 66'	100	
XC315	Orange	3/4" x 66'	100	

## SCOTCHLOK™ ELECTRICAL INSULATION DISPLACEMENT CONNECTORS

- Ideal for controlling circuit wiring, appliance wiring, signal, and PA system or automotive/boat/RV wiring
- Features flame retardant properties
- Designed to connect a wire end to a through wire and insulates the connection
- Insulation Material: Polypropylene
- Connection Type: Run and Tap
- Maximum Operating Temperature: 105°C
- Maximum Recommended Voltage Rating: 600 V
- Conductor Size: 22 - 16 AWG
- Quantity Per Pack: 100



Priced per Pack

Model No.	Mfg. No.	Price /Each
XH543	558-BOX	

## NON-CONTACT VOLTAGE & MAGNETIC FIELD DETECTOR

- AC voltage and magnetic field detector with built-in flashlight
- Check receptacles or insulated wire for presence of AC voltage
- Quickly determine the presence of magnetic fields to determine whether or not components are working properly
- Double insulated housing for increased safety
- Audible (buzzer) and visual (LED) indicators
- Built-in flashlight
- Pocket clip
- Auto shut-off
- Two voltage ranges allow it to detect both high (90 to 1000 V) and low (24 to 1000 V) AC voltage wiring
- Power Supply: (2) AAA Batteries
- Certification(s): CE, IP67, ETL (Conforms to UL STD 61010-1, 61010-2-030, Certified to CSA STD C22.2 No. 61010-1, 61010-2-030)



Model No.	Mfg. No.	Description	Price /Each
IC856	R5120	Non-Contact Voltage & Magnetic Field Detector	

## WIRE TRACER & CIRCUIT TESTING KIT

- Multi-purpose intelligent line tracer/tracker identifies and validates cables from source to termination quickly and accurately
- Test modes include; identifying and locating wires, validating cable/line connections, verifying telephone line continuity/line polarity
- Modular adapters provide direct connection to RJ45 and RJ11 wiring
- Alligator clip adapter allows for easy connection to non-terminated cables
- Adjustable sensitivity wheel improves wire identification and eliminates false detection
- Visual (flashing LEDs) and audible (pulsating beeper) indicators
- Integrated flashlight supports applications in low lit environments
- Built-in non-contact voltage detector
- Earphone jack for loud environments (earphones sold separately)
- Rechargeable batteries
- Low battery indicator and auto shut-off
- Includes: Transmitter, Receiver, Micro-USB charging cable, RJ11 adapter cable, RJ45 adapter cable, RJ11 alligator clip adapter cable, Carrying case
- Certifications: CE, RoHS



Model No.	Mfg. No.	Description	Price /Each
IC752	R5320	Wire Tracer & Circuit Testing Kit	